



V2 POLYMERS

Innovative Materials Suppliers

TEST CERTIFICATE

Grade No: V-PRENE 55A VK 2712F

Batch No: SE0005

PROPERTIES	UNITS	STANDARDS	VALUES
Hardness	Shore A	ISO 868	56
MFI @ 190°C / 2.16 kgs.	Gm/10min	ASTM D1238	2.7
Tensile strength at break <ul style="list-style-type: none">Cross Direction	MPa	ISO 37	5.0
Elongation at break <ul style="list-style-type: none">Cross Direction	%	ISO 37	470
Tear strength <ul style="list-style-type: none">Cross Direction	kN/m	ISO 34	24

Authorized Q. C.
Shirish Patel

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith is believed to be accurate. However, conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that V2 Polymers products are safe, effective, and fully satisfactory for intended end use.

V2 POLYMERS SPECIFICALLY DISCLAIM ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL OR CONSEQUENTIAL DAMAGES.